

PROTEX ACCESSORY INDUSTRIAL LTD.,PART

39/11 Moo.9 Soi Mitmitri27 T. Bangmuangmai

A. Muangsamutprakarn, Samutprakarn 10270, Thailand

TEL.0-2755-5519, 0-2755-5518 FAX.0-2755-5518 www.ProtexGroup2002.com

PROTEX Group

PROTEX ACCESSORY INDUSTRIAL LTD.,PART

PROTEX PLANT STATIONARY ASPHALT MIXING PLANT

MODEL	SAP64	SAP80	SAP120	SAP160
Total Power	154KW	215KW	320KW	399KW
Capacity(under5%aggregate moisture)	64 T/H	80 T/H	120 T/H	160 T/H
Drying drum Length/Diameter	Dai1.20m.x6m.	Dai1.60m.x7.5m.	Dai1.80m.x8m.	Dai2.20m.x9m.
No.of screen layers	4layers	4layers	4layers	5layers
Vibrating screen	Double italy OLI BrandVibrators			
Mixer Capacity	800KG.	1000KG.	1500KG.	2000KG.
Dust Collecting Model	Gravity dust collector +NOMEX Bag House Filter			
Fuel Consumption	≤6.5kg/T finished product			
Fuel type	Heavyoil/Diesel/Coal/NGV/LPG			
Temperature of finished product	140 - 180° C			
Aggregate weighing accuracy	±0.5%Dynamic condition			
Bitumen weighing accuracy	±0.25%Dynamic condition			
Emission Concentration	≤20mg/Nm3			
Heating type of bitumen tank	Hot oil/Electrical			
Finished product hopper	Side Type/Bottom Type (Optional)			